

I have changed Dovecot's mysql connection string. The former was:

```
host=localhost dbname=mailserver user=mailuser pass={your mailuser password}
```

This produces the following error at `/var/log/maillog`:

```
Apr  1 17:54:23 darkstar dovecot: auth: Fatal: mysql: Unknown connect
string: pass
```

The comments in `/etc/dovecot/dovecot-sql.conf.ext` clearly states:

```
# Database connection string. This is driver-specific setting.
...
# mysql:
#   Basic options emulate PostgreSQL option names:
#   host, port, user, password, dbname
```

This is also confirmed by Dovecot's [documentation](#):

```
# The mysqld.sock socket may be in different locations in different systems.
# Use "host= ... pass=foo#bar" with double-quotes if your password has '#'
character.
connect = host=/var/run/mysqld/mysqld.sock dbname=mails user=admin
password=pass
# Alternatively you can connect to localhost as well:
#connect = host=localhost dbname=mails user=admin password=pass
```

I have also followed the advice on double quotes for special characters in the password.

So, the new connection string is:

```
"host=localhost dbname=mailserver user=mailuser password={your mailuser
password}"
```

This change refers to Dovecot v2.2.13.

By the way, I would like to thanks [astrogeek](#) for this article. It's quite precise and clear!

— [Deny Dias](#) 2015/04/01 18:36

From:
<https://docs.slackware.com/> - **SlackDocs**

Permanent link:
https://docs.slackware.com/talk:howtos:network_services:postfix_dovecot_mysql:dovecot

Last update: **2015/04/01 21:40 (UTC)**

